## SH-FLOOD

## Wireless Flood Detector



SH-FLOOD is a two way wireless Flood Detector designed to detect water leaks in kitchens, bathrooms warehouses or yachts. Installation is easy and provides an early warning of developing leaks.





	CROW SH-FLOOD-8F - P/N 0059970	CROW SH-FLOOD V2-8F - P/N 220059970
Detection Method	External golden contacts pins on device	External golden contacts pins on device
	With optional cable of 1.5 meter on bracket	With optional rob of 1.5 meter on bracket
Communication Protocol	Freewave2™ two-way ISM GFSK with 5 frequencies & LBT	
Frequency Band	868MHz	
Identification	Unique ID serial number – 24 bit	
Event Transmission	Alarm, Tamper, Supervision, Low Batt Supervision	
LED Indications	Red LED during alarm	
Tamper Switch	Front Cover Removal	
Supervision Time	7 min by default (programmable between 1 to 30 min)	
Communication Range	500m open space	
Current Consumption	Average: 7uA	
Transmission Current	55mA	
Battery	2x Lithium battery 1.5V AA Energizer L91	
Battery Life	Up to 5 years	
Operating Temperature	−10°C to +55°C	
Dimensions / Weight	63mm x 23.3m x 63mm / 100 gr	
Compliance	CE	