

# FW2-RLY4

## Two Way Wireless Relay for Serenity™ Panels and UART Modules

The FW2-RLY4 is an external two way wireless relay output module with 4 Relays.

It is supported by Crow's Serenity™ control panels and RF-Tx/Rx UART Modules

UP to 3 modules can be used with each panel (e.g. max. 12 programmable Outputs).

### FEATURES

- 4 Relays control
- Push-In wire terminals for easy installation
- Bi-Color LED indication
- Fit in a Universal external plastic box
- Sending Alert/Restore events
- Sending Open/Close Tamper events
- Monitor battery level
- Indicates AC fail (if connected to external power supply)
- Operated by 2 x CR-123 batteries
- Optional external power (from 9V to 12V)



### SPECIFICATION

Operation	Relays	
Protocol	Freewave2™ with AFA and LBT	
Modulation Type	2GFSK	
Frequency Band	868-869MHz / 916-917MHz / 433MHz	
Identification	Unique ID serial number – 24 bit	
Relay Type	Bi-Stable	
Relay contact max capacity	1A / 24V	
Range in open space	500m	
Battery	2 x CR123A	
external power	Option for 9V to 12V	
Battery Life	Batteries only: up to 5 years	External P.S: up to 10 years
Max current	60mA	
Operating Temperature	-10°C to +50°C	
Dimensions	128x70x 27mm	
Weight (incl. battery)	80gr	
Part Number	0034740	