

FW2-RPT

Two Way Wireless Repeater for Serenity™ Panels and UART Modules

The FW2-RPT extends your home alarm system data reception and the RSSI range of your connected devices.

It receives alarm, status and control messages from the wireless devices and sends these messages to the control panel.

It is supported by Crow's Serenity™ control panels and RF- Tx/Rx UART Modules.

PRODUCT FEATURES

- Extends the range of Two Way wireless devices
- AC powered with a six-hour battery back-up
- Secure ID 24 Bits encryption
- Continuously measures communication quality
- Compact and Easy to install
- LED indications for activity and power failure
- Tamper protected
- Available in several frequencies (868MHz / 916MHz) and Voltages



SPECIFICATION

Data Protocol	Freewave2™ Two Way Protocol
Modulation Type	GFSK
Frequency Band	868-869MHz / 916-917MHZ
Identification	Unique ID serial number – 24 bit
Range in open space	500m
Functions	Range Extension Alarm, Tamper, Supervision, Low Bat Compatible with OTA configuration to devices
Power	Designed in compact Plug 230V or 120V Battery Back Up 4.8V rechargeable
Battery Back Up	Up to 10 hours
Operating Temperature	-10°C to +50°C – Indoor Environment
Dimensions	98mm x 73mm x 55mm
Weight (incl. battery)	150grs
Availability	0034360